


CRISTAL 7 PS SG

CADEL

Certificate model name: CRISTAL 7 T2

www.cadelsrl.com



Pellet Air

TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,9 - 7,0
Introduced thermal power (at max)	kW	7,9
Water useful power (at min-at max)	kW	- -
Seasonal energy efficiency	ηs [%]	85
Useful efficiency (at min-at max)	%	90 - 89
Heatable volume (at min-at max)	m³	83 - 200
CO ₂ (min-max)	%	7,8 - 12,0
Emissions CO (13% O ₂) (at min-at max)	mg/Nm³	220 - 125
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm³	2,0 - 2,0
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm³	110 - 99
Dust content at 13% O ₂ (at min-at max)	mg/Nm³	20 - 15
Fuel Pellet	mm	Ø 6 L=3÷40
Hopper capacity	kg	15
Hourly consumption (at min-at max)	kg/h	0,6 - 1,7
Autonomy (at min-at max)	h	25 - 9
Supply and frequency	V-Hz	230-50
Ignition electrical absorption	W	350
Operating electrical absorption (at max)	W	74
Draught for chimney sizing calculation (EN13384-1)	Pa	2
Mass of smoke (at min-at max)	g/sec	3,0 - 5,0
Exhaust fumes temperature (at min-at max)	°C	164 - 239
Distance from material comb. (back/side/under)	mm	200 / 300 / 0
Distance to material comb. (front/top)	mm	650 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	60
Appliance Type (tightness)	Type	CC50

PLUS

5 stars D.M. 186	Back exhaust	Cast iron burning pot
Connection to the external thermostat	Comfort mode - Maximum silence	Shield
Remote control (optional)	Integrated Wi-Fi and Bluetooth	Weekly programming

AVAILABLE FINISHES

7025042	Steel White	EAN 8053859021513
7025043	Steel Red Bordeaux	EAN 8053859021520
7025044	Steel Anthracite	EAN 8053859021537

OPTIONAL

5024010	Remote control with thermostat	EAN 8053859020943
5021001	20° curve kit smoke	EAN 8053859013334
5021002	"T" upper exhaust-kit	EAN 8053859013341
5024001	Upper exhaust kit	EAN 8053859020189

CERTIFICATIONS

European standards
Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



EN 16510-1:2022 / EN 16510-2-6:2022
CE

STOVE PACKAGE

L (cm)	H (cm)	P (cm)
80	117	60
Volume (m³)	0,56	
Gross weight (kg)	66	
Net weight (kg)	56	

STORAGE

N° (max)
2
MAX 2
1

TRANSPORT

66 pz
